

3.3 Fire control panels FC724 (4-loop) in housing (Comfort)

| | | | |
|----------|--------------------------------|--------------------|-----------------|
| FC724-ZA | Fire control panels (4L) | Part no. | S54400-C30-A2 |
| FC724-ZE | Fire control panels (4L, 2LED) | Part no. | S54400-C30-A3 |
| | | Expansion | see chapter 3.4 |
| | | Accessories | see chapter 0 |
| | | Product data sheet | A6V10207176 |

FC724-ZA



- The FC724 is a compact, prefabricated fire control panel with integrated operating unit capable of processing FD720 device signals.
- The fire control panel may be used as a stand-alone unit or networked.
- Up to 16 stations (fire control panels and fire terminals) can be networked via the C-WEB.
- In addition, an Ethernet connection is available at each station. This Ethernet connection enables a maximum of 4 stations inclusive Central Access Point 'CAP' (via Hub) to be networked together (not EN 54-compliant).
- The FXS7212 Cerberus-Engineering-Tool permits the system to be adapted to specific customers' requirements.
- Connection of Siemens Danger Management System via BACnet.
- Ideally suited for mid-size applications, e.g. industrial facilities, regional banks, office complexes, etc. The FC724 can be used by the flexible cross-linking possibilities however also for extensive systems.

Consists of:

- Housing (Comfort)
- Operating unit
- Periphery board
- Power supply 150 W, emergency power supply (batteries must be ordered separately)

FC724-ZE



With 48 indicator groups, with each one red and yellow LED

| | |
|--------------------------------------|----------------------------------|
| Technical data | |
| Mains voltage | 230 VAC |
| Power supply | 150 W |
| Operating voltage | 21... 28.4 VDC |
| Operating current | Max. 5 A |
| Battery capacity | 2 x 12 V, 7... 26 Ah |
| Connectable detector series | Cerberus PRO FD720 (C-NET) |
| Number of lines | 4 (8) loops or 8 (16) stub lines |
| Number of addresses | Max. 504 |
| Relay output | |
| - RT alarm | 1 |
| - RT fault | 1 |
| Monitored outputs | |
| - Alarm | 1 |
| - Fault | 1 |
| - Horn | 2 |
| Free programmable inputs/outputs | 12 |
| Operating temperature | -8... +42 °C |
| Storage temperature | -20... +60 °C |
| Humidity (no condensation permitted) | ≤95 % rel. |
| Dimensions (W x H x D) | 430 x 796 x 160 mm |
| Color | |
| - Housing | grey, ~RAL 7035 |
| - Cover | grey, ~RAL-Design 050 00 00 |
| Protection category | IP30 |
| Approvals VdS / LPCB | pending / pending |